



## SPECIFICATION

- 1. Rated Voltage .....6VDC
- 2. Operating Voltage .....4~8VDC
- 3. Max. Rated Current .....15mA at 6VDC
- 4. Resonant Frequency .....4.8±0.5KHz
- 5. Min. Sound Pressure Level.....85dB at 6VDC/30cm
- 6. Tone Nature .....Continuous
- 7. Shell Material .....PBT
- 8. Operating Temperature .....-20~+80℃
- 9. Store Temperature .....-30~+100℃
- 10. Weight .....6g
- Red(红).....Positive(+)
- Black(黑).....Negative(-)

				<b>KEPO</b> KEPO ELECTRONIC CO., LTD. <a href="http://www.kepo.com.tw">http://www.kepo.com.tw</a>	
				<b>Piezo Buzzer</b>	
				<b>KPI-2210L-06</b>	
<small>No.</small>	<small>DESCRIPTION</small>	<small>APPROVED</small>	<small>DATE</small>		
<small>TOLERANCES UNLESS NOTED OTHERWISE</small> X .+ XX .+ XXX .+ 90° FORMED .2° ANGLES .4° FIRST ANGLE PROJECTION		<small>APPROVALS</small>			
		<small>DRAWN</small>	<small>CHECKED</small>	<small>APPROVED</small>	<small>DATE</small>
				<small>UNIT</small>	<small>DWG NO.</small>
				mm	KP3.840.067
				<small>SCALE</small>	<small>SHEET</small>
				05.02.29	VER 1.2