

K32 (S32) THRU K320 (S320)

Surface Mount General Purpose Rectifier


● Essential information; basic information

<p>Features</p> <ul style="list-style-type: none"> ● Low profile package ● Ideal for automated placement ● Guardring for overvoltage protection ● Low power losses, high efficiency ● High forward surge capability ● Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C <p>Typical Applications</p> <p>For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.</p> <p>Mechanical Data</p> <ul style="list-style-type: none"> ● Package: SOD-123FL Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant ● Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102 ● Polarity: Cathode line denotes the cathode end 	
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

● Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	S32	S34	S36	S38	S310	S315	S320
			K32	K34	K36	K38	K310	K315	K320
Maximum Repetitive peak reverse voltage	VRRM	V	20	40	60	80	100	150	200
Average rectified output current@60Hz sine wave, resistance load, TL (Fig.1)	IO	A	3.0						
Forward Surge Current (Non-repetitive)@60Hz Half-sine wave, 1 cycle, Tj=25°C	IFSM	A	65						
Storage temperature	Tstg	°C	-55 ~ +125						
Junction temperature	Tj	°C	-55 ~ +125			-55 ~ +150			
Maximum instantaneous forward voltage drop per diode	VF (IFM=3.0A)	V	0.6		0.7	0.85		0.9	
Maximum DC reverse current at rated DC blocking voltage per diode @VRM=VRRM	IR (Tj=25°C)	mA	0.5			0.1			
	IR (Tj=100°C)		10			5			


● Characteristics (Typical)



● Ordering Information (Example)

type specification	manner of packin	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S32-S320	T/B	3000	24000	240000	7" reel
K32-K320 (SOD-123FL)		10000	30000	300000	13" reel

● **Outline Dimensions**



SOD-123FL		
Dim	Min	Max
A	1.60	1.90
B	0.90	1.10
C	2.55	2.85
D	3.60	3.90
E	1.00	1.20
F	0.40	0.90
G	0.10	0.25
H	0.02	0.05

● **Disclaimer**

The information presented in this document is for reference only. right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), chenglitai or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. or consult your nearest chenglitai's sales office for further assistance.