



HIGH CURRENT SURFACE-MOUNT POWER INDUCTORS

FASDR SERIES

0302,0403,0504,0703,0705,1004,1005

FEATURES:

- Current up to 6.8A
- Larg Current
- Flat-top for Pick & Place
- Low cost

OPTIONS:

- Tape & Reel is Standard
- Bulk Packaging Available for Smaller Quantities
- Tolerance:10% and 20% is Standard
- Custom Design Available

COMMON APPLICATIONS:

- Ideal for Palm-Top and Laptop DC-DC Converters
- PDA's Flash Memory
- Step-up,Step-down Converters
- Top-box

STANDARD SPECIFICATION:


Part Number	Inductance H	DCR()										IDC(A) Max									
		FASDR0302	FASDR0403	FASDR0503	FASDR0504	FASDR0703	FASDR0705	FASDR1004	FASDR1005	FASDR1008	FASDR0302	FASDR0403	FASDR0503	FASDR0504	FASDR0703	FASDR0705	FASDR1004	FASDR1005	FASDR1008		
1R0	1.0	0.07	0.049	0.03	0.028						2.080	2.560	4.500	3.000							
1R4	1.4	0.09	0.057	0.04	0.029						1.860	2.520	4.000	2.800							
1R8	1.8	0.11	0.064	0.05	0.030						1.800	1.950	3.300	2.600							
2R2	2.2	0.13	0.072	0.06	0.042						1.390	1.750	2.940	2.300							
2R7	2.7	0.14	0.079	0.07	0.044						1.320	1.580	2.500	2.100							
3R3	3.3	0.20	0.087	0.08	0.045						1.250	1.440	2.350	2.000							
3R9	3.9	0.21	0.094	0.09	0.047						1.200	1.330	2.200	1.950							
4R7	4.7	0.33	0.109	0.14	0.048						1.030	1.150	2.000	1.900							
5R6	5.6	0.35	0.126	0.15	0.050						0.910	1.100	1.800	1.800							
6R8	6.8	0.38	0.132	0.16	0.060						0.850	1.080	1.700	1.600							
8R2	8.2	0.43	0.147	0.17	0.090						0.820	1.050	1.400	1.500							
100	10	0.50	0.182	0.18	0.10	0.08	0.07	0.05	0.06	0.036	0.740	1.040	1.200	1.440	1.440	2.300	2.380	2.600	4.050		
120	12	0.65	0.210	0.20	0.12	0.09	0.08	0.06	0.07	0.038	0.640	0.970	1.180	1.400	1.390	2.000	2.130	2.450	3.600		
150	15	0.82	0.235	0.22	0.14	0.10	0.09	0.07	0.08	0.04	0.600	0.850	1.150	1.300	1.240	1.800	1.870	2.270	3.340		
180	18	0.90	0.338	0.25	0.15	0.11	0.10	0.08	0.09	0.05	0.540	0.740	1.100	1.230	1.120	1.600	1.730	2.150	3.050		
220	22	1.14	0.378	0.35	0.18	0.13	0.11	0.09	0.10	0.06	0.500	0.680	1.000	1.110	1.070	1.500	1.600	1.950	2.800		
270	27	1.39	0.522	0.45	0.20	0.15	0.12	0.10	0.11	0.07	0.430	0.620	0.860	0.970	0.940	1.300	1.440	1.760	2.500		
330	33	1.55	0.540	0.56	0.23	0.17	0.13	0.12	0.12	0.08	0.400	0.560	0.760	0.880	0.850	1.200	1.260	1.500	2.400		
390	39	2.15	0.587	0.698	0.32	0.22	0.16	0.15	0.14	0.09	0.370	0.520	0.750	0.800	0.740	1.100	1.200	1.370	2.200		
470	47	2.44	0.844	0.72	0.37	0.25	0.18	0.17	0.17	0.11	0.360	0.440	0.730	0.720	0.680	1.100	1.100	1.280	2.000		
560	56	2.68	0.937	0.84	0.42	0.28	0.24	0.20	0.19	0.12	0.310	0.420	0.550	0.680	0.640	0.940	1.010	1.170	1.900		
680	68	3.05	1.117	0.90	0.46	0.33	0.28	0.22	0.22	0.15	0.300	0.370	0.520	0.610	0.590	0.850	0.910	1.110	1.800		
820	82	3.48	1.200	0.95	0.60	0.41	0.37	0.25	0.25	0.19	0.280	0.300	0.500	0.580	0.540	0.780	0.850	1.000	1.600		
101	100	3.84	1.440	1.30	0.70	0.48	0.43	0.34	0.35	0.23	0.250	0.280	0.400	0.520	0.510	0.720	0.740	0.970	1.500		
121	120	5.76	1.660	1.38	0.93	0.54	0.47	0.40	0.40	0.32	0.200	0.240	0.360	0.480	0.490	0.660	0.690	0.890	1.400		
151	150	6.62	1.880	1.81	1.10	0.75	0.64	0.54	0.47	0.37	0.190	0.220	0.300	0.400	0.400	0.580	0.610	0.780	1.300		
181	180	7.36	2.180	1.95	1.38	1.02	0.71	0.62	0.63	0.42	0.170	0.210	0.260	0.380	0.360	0.510	0.560	0.720	1.200		
221	220	8.38	2.570	2.10	1.57	1.20	0.96	0.72	0.73	0.44	0.160	0.200	0.250	0.350	0.310	1R0	0.530	0.660	1.000		
271	270	13.69	3.520	2.42	1.85	1.31	1.11	0.95	0.97	0.55	0.140	0.180	0.210	0.280	0.290	0.420	0.450	0.570	0.950		
331	330	15.78	5.000	3.82	2.00	1.50	1.26	1.10	1.15	0.60	0.130	0.120	0.180	0.260	0.280	0.400	0.420	0.520	0.900		
391	390	17.40	6.000	4.68	2.60	2.700	1.77	1.24	1.30	0.67	0.120	0.115	0.160	0.240	0.270	0.360	0.380	0.480	0.800		
471	470	20.00	7.000	5.10	3.00	3.000	1.96	1.53	1.48	0.88	0.084	0.110	0.150	0.220	0.250	0.340	0.350	0.420	0.700		
561	560			6.00	4.19			1.80	1.90	1.04			0.140	0.180			0.320	0.330	0.650		
681	680			7.60	4.44				2.25	1.18			0.130	0.160				0.280	0.600		
821	820			9.12	5.12				2.55	1.38			0.070	0.110			0.240	0.500			
102	1000			9.87	10.00					1.74			0.050	0.080				0.480			
122	1200									1.92									0.380		

TECHNICAL INFORMATION:

- TEST FREQ.(L) with HP4284A and HP4285A (equivalent acceptable)
1.0-8.2 H(7.95MHz) 10-82 H(2.52MHz) 100-1200 H(1KHz)
- Tolerance of inductance
FASDR0302 1.0-470 H 20%(M)
FASDR 0403 1.0-27 H 20%(M) 33-470 H 10%(K)
FASDR0503 1.0-2.7 H 20%(M) 33-1000 H 10(K)
FASDR0504 1.0-27 H 20%(M) 33-47 H 15%(L) 56-1000 H 10%(K)
FASDR0703 10-47 H 20%(M) 56-470 H 10%(K)
FASDR 0705 10-470 H 20%(M)
FASDR1004 10-47 H 20%(M) 56-560 H 10%(K)
FASDR1005 10-39 H 20%(M) 47-820 H 10%(K)
FASDR1008 10-82 H 20%(M) 100-1200 H 10%(K)
- DCR: GW813 or QuadTech 1880 Milliohm meter
- IDC Max is decreased 10% against its initial value

Operating Temperature:-40 to+85
Storage Temperature:-40 to +105
Solder methods: Vapor Phase,Infrared Reflow
Resistance to soldering heat:260 for 10 seconds
Solvent resistance: Conforms to MIL-STD-202E
Marking: Inductance & Tolerance
Note:All specification subject to change without noticed.

CHARACTERISTICS:



TYPE	A	B	C	D
FASDR 0302	3.0 0.3	2.8 0.3	2.5 0.3	0.8
FASDR 0403	4.5 0.3	4.0 0.3	3.2 0.3	1.3
FASDR 0503	5.8 0.3	5.2 0.3	2.5 0.3	1.3
FASDR 0504	5.8 0.3	5.2 0.3	4.5 0.3	1.3
FASDR 0703	7.8 0.3	7.0 0.3	3.5 0.3	2.1
FASDR 0705	7.8 0.3	7.0 0.3	5.0 0.3	2.1
FASDR 1004	10.0 0.3	9.0 0.3	4.0 0.3	2.1
FASDR 1005	10.0 0.3	9.0 0.4	5.4 0.3	2.1
FASDR 1008	11.0Max	10.0Max	7.5Max	2.1
FASDR 1008	11.0Max	10.0Max	8.5Max	2.1