

MATERIAL SPECIFICATION

MATERIAL SAFETY DATA SHEET

SECTION 1 CHEMICAL PRODUCT

MSDS Name	Leaded Solder Wire
Product Description	ПОО 40, ПОО 60/61, 0.5MM-2.0MM, 10G-1000G
Composition	Tin/Lead
Product Type	NO FLUX / SOLID
Diameter	0.5/0.8/1.0/1.2/1.5/2.0MM
Weight	10/12/20/50/100/200/250/500/1000G

SECTION 2 COMPOSITION, INFORMATION ON INGREDIENTS

MSDS Product Name	Leaded Solder Wire			
Material Chemical Type	Welding			
Composition	CAS #	OSHA PEL (mg/m ³)	TLV-TWA (mg/m ³)	TLV-STEL (mg/m ³)
Sn	7440-31-5	2.0	2.0	N/A
Pb	7439-92-1	0.1	0.2	N/A

SECTION 3 HAZARDS IDENTIFICATION

Health Hazards	Acute Stimulate an eye skin, and upper respiratory track.
Safety Hazards	Causes severe burns. Risk of serious damage to eyes. Limited evidence of a carcinogenic effect.

Symptoms and consequences	Headache,Dizziness, nausea and anaesthesia. Irritate skin, eyes and respiratory tract. Dry skin
Inhalation	Turn to fresh air, if worse, seek medical care immediately.
Skin	Clean skin by soap and water, if worse, seek medical care immediately.
Eyes	Wash by water in 10 minutes immediately, if worse, seek medical care.
Ingestion	Do not vomit, drink if possible, if worse, seek medical care.

SECTION 5 FIRE FIGHTING MEASURES

Fire extinguishing measure and extinguishing media	CO-blanket, chemical dey powder, alcohol resistant foam. Soil/ Sand only when little fire.
Personal Protection	Respiratory protection must be worn.
Others	Cool down the machine nearby by Showering.

SECTION 6 LEAK HANDLING

General Information	Exclude sources of ignition and ventilate the area. Isolate from sources of heat, sparks and open flame.
Personal Protection	Wear protective clothing for all parts of the body.
Spill/Leak	Do not allow to enter drains or watercourses and place in container for disposal according to local regulations..

SECTION 7 HANDLING AND STORAGE

Handling	Do not allow to enter drains or watercourses.
Storage	In Fresh air.
Storage tempreature	25°C

SECTION 8 SPECIAL PROTECTION INFORMATION

Breath protection (Specify type)	There is enough ventilation did not require under normal circumstances
Local exhaust	Yes

Machine(Ordinary)	Yes
Special announcement	Not applicable
Protective gloves	Rubber, Neoprene,PVC or Equivalent

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Form	Solid
Color	Silver and white
Odour	Odourless
Boiling Point	Not Applicable
Melting Point	183-227°C
Density (20 °C)	8.5g/cm ³

SECTION 10 STABILITY AND REACTIVITY

Stability	Stable under normal condition
Condition	Fire and spark
Taboo	Strong Oxidant
Hazardous Decomposition Products	None

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Toxicity Oral	Hypo toxicity , LD50 > 2000mg/kg
Acute Toxicity Skin	Hypo toxicity , LD50 > 2000mg/kg
Acute Toxicity Inhalation	Hypo toxicity , LD50 > 5mg/L
Skin Irritation	Slight irritation under permission of EU
Eye Irritation	Irritate
Skin Sensation	Part of Sensation
Repeated-dose Toxicity	Repeated exposures do not cause significant toxic reactions.
Mutagenicity	None
Influence	Repeated inhalation may cause dermatitis, irritation of eye and respiratory system and paralysis

SECTION 12 DISPOSAL CONSIDERATION

Waste Treatment	Recycling or reuse
Product Treatment	Recycling or reuse
Local Law Information	Dispose the waste according to the local regulations.

SECTION 13 ECOLOGICAL DATAS

Flex	Avoid release to soil in Liquid Form. If so, it may pollute underground water.
Toxicity to Fish	None, LD/EC/IC50 > 1000mg/L
To Aquatic invertebrates	None, LC/EC/IC50 > 1000mg/L
Dirty treatment	None, LC/EC/IC50 > 1000mg/L
Other	This product is not going to cause any toxicity to the aquatic environment.

SECTION 14 TRANSPORTATION DATA

Classification	Not applicable
Hazardous Marks	Not applicable
Packaging	Not applicable
ICAO U.N.no.	Not applicable

SECTION 15 REGULATION INFORMATION

1) EC Dangerous Classification
(R36/37) Eye and skin irritation (R20/R21) Hazard with inhalation and ingestion (R38) Irritate to skin
2) EC Safety No.
(S9) Storage in fresh air. (S16) Avoid fire - No smoking. (S24/25) Avoid contact to skin and eye (S33) Precaution to ESD and EOS
(S36) Wear protective clothes (S43A) Put out fire with sand, soil, chemical powder and foam.