


SECTION A-A(K41)  
Material: Copper



SECTION A-A(K41)  
Material: Copper

Pin	Cable color	Pin	Cable color
1	Brown	6	Blue
2	Red	7	Purple
3	Orange	8	Groy
4	Yellow	9	White
5	Green	10	Black

Number	Dimensions		
	TP(mm)	W(mm)	Tolerance
10	11.43	12.70	±0.30

- Notes:**
- Insulation material: PVC  
Color: Gray
  - Specifications:  
Rating : 300V  
Conductor Size: 28-30AWG  
Insulation resistance: 100MΩ/km min.
  - Applications:  
Internal wiring of computers , electronic exchanges , measurement control devices , business machines , communication devices, and other electronic equipment.

**Order information**

FRC-10-MULTI: 7-Ø0.100 (30AWG)  
 FRC-10-MULTI 28AWG: 7-Ø0.127 (28AWG)  
 Max conductor resistance DC at 20°C Ohm/m:  
 Ø 0.100 < 0.397  
 Ø 0.127 < 0.237

Total Pitch Tolerances		Nominal dimension range													
In mm		In mm													
over	to	over	to	over	to	over	to	over	to	over	to	over	to	over	to
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	250
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	CXL	DATE	14.06.06	UNITS	mm
CHK	DATE	SCALE	1 : 1	SHEET/OF	A4
APP.	DATE	NAME	FRC-10-MULTI		
DWGNO					1 / 1

