

Performance:

Soft, insulated

Ratio: 3:1

 Axial shrinkage  $\leq \pm 5\%$ 

Shrink Temp.: 90°C

Working temp.: -40°C~125°C

### 3:1 Environment Friendly Dual Wall Heat Shrinkable Tube

Datasheet SBRS (3X) Specification							
Размер	До усадки (mm)	После усадки (mm)			Стандарт упаковки		Сфера применения
Size	Before Shrinkage	After Shrinkage			Packaging standard		Application Range
mm	Мин. диаметр	Макс. диаметр	Толщина стенки	Толщина клеевого слоя	м/рулон	М/шт	(mm)
	Min I.D.	Max I.D.	Total W.T.	Adhesive thickness	m/spool	m/pc	
Φ 2.4	≥ 2.4	≤ 1.0	0.70±0.15	0.35±0.10	200	—	1.0-2.3
φ 3.2	≥ 3.2	≤ 1.30	0.90±0.30	0.40±0.20	200	—	1.3-3.1
φ 4.8	≥ 4.8	≤ 1.70	1.05±0.30	0.40±0.20	100	—	1.8-4.6
φ 6.4	≥ 6.4	≤ 2.50	1.25±0.30	0.45±0.20	100	—	2.5-6.4
φ 7.9	≥ 7.9	≤ 2.80	1.30±0.30	0.45±0.20	100	—	2.9-7.7
φ 9.5	≥ 9.5	≤ 3.20	1.45±0.30	0.50±0.20	50	1.22	3.4-9.4
φ 12.7	≥ 12.7	≤ 4.60	1.70±0.30	0.50±0.20	—	1.22	4.8-12.5
φ 15.0	≥ 15.0	≤ 5.60	1.80±0.30	0.55±0.30	—	1.22	5.8-14.8
φ 19.1	≥ 19.1	≤ 6.80	1.95±0.30	0.60±0.30	—	1.22	7.0-18.8
φ 25.4	≥ 25.4	≤ 9.50	2.05±0.40	0.60±0.30	—	1.22	9.7-25.0
φ 30.0	≥ 30.0	≤ 12.00	2.20±0.40	0.65±0.30	—	1.22	12.3-30.0
φ 39.0	≥ 39.0	≤ 15.00	2.50±0.40	0.75±0.30	—	1.22	15.5-39.0
φ 50.0	≥ 50.0	≤ 19.00	2.80±0.40	0.80±0.30	—	1.22	19.5-49.0
φ 60.0	≥ 60.0	≤ 23.00	3.20±0.40	1.05±0.30	—	1.22	23.5-58.0
φ 75.0	≥ 76.0	≤ 25.00	3.20±0.50	1.05±0.40	—	1.22	26.0-72.0
φ 90.0	≥ 90.0	≤ 33.00	3.30±0.50	1.05±0.40	—	1.22	35.0-88.0
φ 100.0	≥ 100	≤ 34.00	3.8±0.50	1.20±0.40	25	1.22	35-100
φ 125.0	≥ 125	≤ 42.00	3.8±0.50	1.20±0.40	25	1.22	43-125
φ 130.0	≥ 130	≤ 44.00	3.8±0.50	1.20±0.40	25	1.22	45-130